## NSN 5930-01-220-9828

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-220-9828 **Body Style:** Hole mounted **Actuator Style:** Round **Actuator Diameter:** 0.330 inches **Actuator Height:** 1.047 inches **Actuator Free Position Height:** 1.797 inches **Housing Height:** 1.750 inches **Housing Length:** 3.040 inches **Housing Width:** 1.000 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 0.917 inches **Maximum Voltage Rating In Volts:** 480.0 ac and 250.0 dc **End Application:** Power hacksaw **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Features Provided:** Actuator seal **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Actuating Force:** Between 9.0 ounces and 24.0 ounces **Actuator Movement:** Between 0.078 pretravel inches and 0.219 overtravel inches and 0.002 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 0.250 amperes resistive dc and 15.000 amperes resistive ac **Terminal Type And Quantity:** 3 screw Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5930-01-220-9828

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0