NSN 5930-01-221-2359

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-221-2359

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
3.086 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator
Actuator Inscription:
Crew call single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Panel, indicator, direction finder id-2302/alq-15 (v)
Mounting Surface To Terminal End Distance:
2.996 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:

Nonpile-up Contact Arrangement:

Full display lens and holding mechanism

3 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit

NSN 5930-01-221-2359

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Special Features:

Emi shielded

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0