# NSN 5930-01-221-6841

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-221-6841



### **Body Style:**

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

4.300 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Case Material:

Metal

# Actuator Length:

0.620 inches

Actuator Style:

# Rectangular

Actuator Height:

#### 0.100 inches

Actuator Width:

0.620 inches

#### Actuator Color:

Black single actuator

#### **Illuminated Actuator Color:**

Green single actuator

#### Actuator Inscription:

On avail single actuator

#### Maximum Voltage Rating In Volts:

28.0 dc and 115.0 ac

#### Mounting Surface To Terminal End Distance:

4.200 inches

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

#### Features Provided:

Full display lens and holding solenoid

#### Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

NSN 5930-01-221-6841

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

# **Precious Material And Location:**

Contacts silver

# Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

Fiig:

A053a0