

View Online at <https://aerobasegroup.com/nsn/5930-01-221-8140>

Thread Class:

2a single mounting facility

Thread Length:

0.240 inches single mounting facility and 0.260 inches single mounting facility

Overall Length:

1.225 inches

First Flat Length:

0.240 inches single actuator and 0.260 inches single actuator

Flat Height:

0.084 inches single actuator and 0.104 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.302 inches single actuator and 0.322 inches single actuator

Overall Diameter:

Between 0.547 inches and 0.577 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

End Application:

5820-01-145-8305 receiver-transmitter, radio rt-1402/g

Switch Contact Basic Design:

Coded

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Rfi shielding

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Detent Rotational Torque Range:

+4.900/+9.100 inch-ounces single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level

Contact Arrangement Truth Table:

Bcd, 1 pole - 8 positions single section

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0