

View Online at <https://aerobasegroup.com/nsn/5930-01-221-8140>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.240 inches single mounting facility and 0.260 inches single mounting facility

**Overall Length:**

1.225 inches

**First Flat Length:**

0.240 inches single actuator and 0.260 inches single actuator

**Flat Height:**

0.084 inches single actuator and 0.104 inches single actuator

**Shaft Diameter:**

0.123 inches single actuator and 0.126 inches single actuator

**Shaft Length:**

0.302 inches single actuator and 0.322 inches single actuator

**Overall Diameter:**

Between 0.547 inches and 0.577 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 3: 00 o'clock

**End Application:**

5820-01-145-8305 receiver-transmitter, radio rt-1402/g

**Switch Contact Basic Design:**

Coded

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Features Provided:**

Rfi shielding

**Thread Size:**

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from contact position 1 single actuator

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Printed circuit

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Detent Rotational Torque Range:**

+4.900/+9.100 inch-ounces single actuator

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level

**Contact Arrangement Truth Table:**

Bcd, 1 pole - 8 positions single section

**Style Designator:**

Snap or line

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0