NSN 5930-01-221-8145

Rotary Switch Section - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-221-8145

Hazardous Locations/environmental Protection:
Shock proof and vibration proof
Overall Height:
1.328 inches
Overall Width:
1.297 inches
Body Thickness:
0.120 inches
Unthreaded Mounting Hole Diameter:
0.115 inches single mounting facility
Distance Between Mounting Facility Centers:
1.031 inches single mounting facility
Operating Tempurature Range:
-65.0 to 85.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section rear
Throw Quantity:
4 single section front
Mounting Method:
Strut and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Terminal Type:
Clip
Contact Switching Action:
Makes before breaks single section front
Contact Load Current Rating:
500.0 milliamperes resistive load and 50.0 milliamperes inductive load dc at sea level
Precious Material And Location:
Terminals and rotor blades silver
Precious Material:
Silver
Style Designator:
Switch section, rotary
Switch section, rotary Shelf Life:

--

NSN 5930-01-221-8145

Rotary Switch Section - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0