NSN 5930-01-221-8145

Rotary Switch Section - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-221-8145

Hazardous Locations/environmental Protection:

Shock proof and vibration proof

Overall Height:

1.328 inches

Overall Width:

1.297 inches

Body Thickness:

0.120 inches

Unthreaded Mounting Hole Diameter:

0.115 inches single mounting facility

Distance Between Mounting Facility Centers:

1.031 inches single mounting facility

Operating Tempurature Range:

-65.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

4 single section front

Mounting Method:

Strut and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Terminal Type:

Clip

Contact Switching Action:

Makes before breaks single section front

Contact Load Current Rating:

500.0 milliamperes resistive load and 50.0 milliamperes inductive load dc at sea level

Precious Material And Location:

Terminals and rotor blades silver

Precious Material:

Silver

Style Designator:

Switch section, rotary

Shelf Life:

N/a

Unit Of Measure:

NSN 5930-01-221-8145

Rotary Switch Section - Page 2 of 2

Demilitarization:

No

Fiig:

A052b0

