## NSN 5930-01-221-8163

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-221-8163

**Body Style:** 

Panel mounted

**Overall Length:** 

2.751 inches

**Overall Height:** 

0.750 inches

Overall Width:

0.750 inches

Body Width:

0.688 inches

**Body Height:** 

0.688 inches

Actuator Length:

0.620 inches

Actuator Style:

### Rectangular

Actuator Height:

0.090 inches

Actuator Width:

0.620 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

#### Actuator Inscription:

Crew call single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Panel, indicator, countermeasures id-2300/alq-15 (v)

Mounting Surface To Terminal End Distance:

2.446 inches

Inclosure Type:

Fully enclosed

**Mounting Method:** 

Panel

**Features Provided:** 

Holding mechanism

Nonpile-up Contact Arrangement:

 $\ensuremath{\mathsf{3}}$  pole, double throw, both positions maintained single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

# NSN 5930-01-221-8163

Push Switch - Page 2 of 2

Special Features:

Emi shielded

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

9 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

