

View Online at <https://aerobasegroup.com/nsn/5930-01-221-9980>

Thread Class:

2a single mounting facility

Thread Length:

0.235 inches single mounting facility and 0.265 inches single mounting facility

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

Between 1.184 inches and 1.284 inches

First Flat Length:

0.240 inches single actuator and 0.260 inches single actuator

Flat Height:

0.084 inches single actuator and 0.104 inches single actuator

Shaft Diameter:

0.123 inches single actuator and 0.126 inches single actuator

Shaft Length:

0.302 inches single actuator and 0.332 inches single actuator

Overall Diameter:

Between 0.485 inches and 0.515 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 3: 00 o'clock

Operating Temperature Range:

-65.0/+125.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Features Provided:

Rfi shielding

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Printed circuit

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level and 100.0 milliamperes lamp load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0