## NSN 5930-01-222-0880



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-222-0880 **Thread Class:** 2a **Body Style: Bushing mounted Overall Length:** 0.500 inches **Overall Height:** 1.188 inches **Overall Width:** 0.270 inches **Bushing Length:** 0.280 inches **Body Length:** 0.500 inches **Body Width:** 0.270 inches **Body Height:** 0.410 inches **Case Material:** Plastic **Actuator Diameter:** 0.122 inches **Actuator Height:** 0.248 inches **Maximum Voltage Rating In Volts:** 120.0 ac and 28.0 dc **End Application:** 5895-01-147-4767 satellite configura **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi):

40

**Thread Size:** 

0.250 inches

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:** 

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Precious Material And Location:** 

Contact and terminal surfaces gold

## NSN 5930-01-222-0880

Push Switch - Page 2 of 2



Thread Series Designator:
Uns
Terminal Type And Quantity:
3 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0