

View Online at <https://aerobasegroup.com/nsn/5930-01-222-3692>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Humidity resistant

Overall Length:

Between 12.0 millimeters and 14.0 millimeters

Overall Height:

Between 31.0 millimeters and 36.0 millimeters

Overall Width:

Between 10.5 millimeters and 14.0 millimeters

Bushing Length:

Between 7.5 millimeters and 8.5 millimeters

Body Length:

Between 12.0 millimeters and 14.0 millimeters

Body Width:

Between 10.5 millimeters and 14.0 millimeters

Actuator Style:

Rectangular

Actuator Height:

Between 10.5 millimeters and 12.5 millimeters

Actuator Width:

5.0 millimeters

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac

End Application:

6625-01-154-4844 test set modular

Mounting Surface To Terminal End Distance:

Between 13.0 millimeters and 15.0 millimeters

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded bushing

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac

Precious Material And Location:

Contact and terminal surfaces silver

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0