

View Online at <https://aerobasegroup.com/nsn/5930-01-222-3692>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Humidity resistant

**Overall Length:**

Between 12.0 millimeters and 14.0 millimeters

**Overall Height:**

Between 31.0 millimeters and 36.0 millimeters

**Overall Width:**

Between 10.5 millimeters and 14.0 millimeters

**Bushing Length:**

Between 7.5 millimeters and 8.5 millimeters

**Body Length:**

Between 12.0 millimeters and 14.0 millimeters

**Body Width:**

Between 10.5 millimeters and 14.0 millimeters

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 10.5 millimeters and 12.5 millimeters

**Actuator Width:**

5.0 millimeters

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac

**End Application:**

6625-01-154-4844 test set modular

**Mounting Surface To Terminal End Distance:**

Between 13.0 millimeters and 15.0 millimeters

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded bushing

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac

**Precious Material And Location:**

Contact and terminal surfaces silver

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0