## NSN 5930-01-222-6650

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-222-6650
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.000 inches
First Flat Length:
0.500 inches single actuator
Flat Height:
0.310 inches single actuator and 0.312 inches single actuator
Shaft Diameter:
0.369 inches single actuator and 0.373 inches single actuator
Shaft Length:
0.880 inches single actuator
Overall Diameter:
6.750 inches
Unthreaded Mounting Hole Diameter:
0.380 inches single mounting facility
Individual Section Quantity:
2
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 each section front
Throw Quantity:
2 each section front
Mounting Facility Circle Radius:
3.310 inches single mounting facility
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob and legend plate
Contact Voltage Rating In Volts:
500.0 ac at sea level
Rotor Through Connection Quantity:
2 each section
Mounting Facility Pattern:
Three position circular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Round, flatted w/through hole single actuator

Terminal Type:

Tab w/screw

## NSN 5930-01-222-6650

Rotary Switch - Page 2 of 2

A052b0



Contact Switching Action:
Breaks before makes each section front
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:
30.0 amperes resistive load dc at sea level
Special Features:
Switch is in enclosed box
Style Designator:
Tap, circular, bushing mount
Test Data Document:
81349-mil-s-15743 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-s-15743/8 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: