NSN 5930-01-222-8095

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-222-8095

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
8.031 inches
Overall Height:
3.062 inches
Overall Width:
3.250 inches
Actuator Style:
Roller plunger
Actuator Free Position Height:
1.906 inches
Actuator Roller Diameter:
1.000 inches
Actuator Roller Width:
0.250 inches
Housing Height:
3.062 inches
Housing Length:
6.125 inches
Housing Width:
3.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
5.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
2.375 inches
Maximum Voltage Rating In Volts:
440.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:

Actuator Movement:

Between 0.310 pretravel inches and 0.158 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.500 amperes resistive dc and 1.500 amperes resistive ac

Special Features:

Non-magnetic

NSN 5930-01-222-8095

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0