

View Online at <https://aerobasegroup.com/nsn/5930-01-222-8700>

**Thread Class:**

2a single threaded stud

**Thread Length:**

0.054 inches single threaded stud

**Overall Length:**

0.373 inches

**Body Length:**

0.170 inches

**End Application:**

4920-01-121-9954 evacuation and fill station

**Temperature Sensing Element Type:**

Internal sensor

**Width Across Flats:**

0.281 inches

**Operating Temperature Rating:**

Between -30.0 degrees fahrenheit and 365.0 degrees fahrenheit

**Mounting Method:**

Threaded stud

**Features Provided:**

Hermetically sealed case and internally grounded

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single threaded stud

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

1.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

250.00 actuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Plug

**Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf single threaded stud

**Specification Data:**

81349-mil-s-24236/19 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0