## NSN 5930-01-222-9467

Thermostatic Switch - Page 1 of 2

Silver



View Online at https://aerobasegroup.com/nsn/5930-01-222-9467

**Thread Class:** 2a single threaded stud **Thread Length:** 0.500 inches single threaded stud **Hazardous Locations/environmental Protection:** Salt spray resistant and vibration resistant **Overall Height:** 1.087 inches **Body Height:** 0.481 inches **Overall Diameter:** 0.625 inches **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** 350.0 degrees fahrenheit **Mounting Method:** Threaded stud **Features Provided:** Hermetically sealed case **Contact Action Stimulus:** Increase **Thread Size:** 0.190 inches single threaded stud **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load first voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 179.00 actuation point degrees fahrenheit and 194.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage Media For Which Designed: Gas **Precious Material And Location:** Contacts silver **Precious Material:** 

## NSN 5930-01-222-9467

Thermostatic Switch - Page 2 of 2



Style Designator:
Disc
Thread Series Designator:
Unf single threaded stud
Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A048b0