

View Online at <https://aerobasegroup.com/nsn/5930-01-223-1546>

Thread Class:

2a single mounting facility

Thread Length:

0.470 inches single mounting facility

Overall Length:

6.630 inches

Overall Diameter:

2.000 inches

Nonturn Device Radius:

0.380 inches at 12: 00 o'clock

Individual Section Quantity:

10

Nonturn Device Type:

Tab at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes inductive load ac at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Test Data Document:

81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns single mounting facility

Specification Data:

81349-mil-s-21604/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0