

View Online at <https://aerobasegroup.com/nsn/5930-01-223-3090>

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Actuator Style:

Roller plunger

Actuator Free Position Height:

1.650 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.100 inches

Housing Diameter:

1.000 inches

Housing Length:

1.840 inches

Housing Bushing Length:

0.800 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 160.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0