## NSN 5930-01-223-6414

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-223-6414

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

7.860 inches

**Overall Height:** 

2.910 inches

**Overall Width:** 

2.810 inches

**Individual Section Quantity:** 

6

**Longest Horizontal Distance Between Mounting Centers:** 

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:** 

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

2.187 inches single mounting facility

**Operating Tempurature Range:** 

-25.0/+125.0 degrees fahrenheit

**End Application:** 

6115-00-450-5881 generator set d

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded hole single mounting facility

**Features Provided:** 

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

24 single mounting facility

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:** 

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Makes before breaks each section periphery

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

## NSN 5930-01-223-6414

Rotary Switch - Page 2 of 2

No Fiig: A052b0



## **Switch Actuator Stop Device Type:** Fixed stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load highest ac voltage rating at sea level **Precious Material And Location:** Contact and terminal surfaces silver **Precious Material:** Silver Style Designator: Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization: