NSN 5930-01-223-6414

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-223-6414

Thread Class:

2b single mounting facility

Overall Length:

7.860 inches

Overall Height:

2.910 inches

Overall Width:

2.810 inches

Individual Section Quantity:

6

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.187 inches single mounting facility

Operating Tempurature Range:

-25.0/+125.0 degrees fahrenheit

End Application:

6115-00-450-5881 generator set d

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

NSN 5930-01-223-6414

Rotary Switch - Page 2 of 2

No Fiig: A052b0



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 5.0 amperes resistive load highest ac voltage rating at sea level **Precious Material And Location:** Contact and terminal surfaces silver **Precious Material:** Silver Style Designator: Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization: