NSN 5930-01-223-6415

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-223-6415

Hazardous Locations/environmental Protection:

Moisture resistant and dust resistant and salt spray resistant

Overall Length:

3.260 inches

Overall Height:

1.770 inches

Overall Width:

1.150 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

3.090 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Operating Tempurature Range:

-25.0 to 150.0 degrees fahrenheit

End Application:

5895-01-108-5631 satellite comm term

Pole Quantity:

1 each section in-line

Throw Quantity:

10 each section in-line

Mounting Method:

Bracket and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Printed circuit

Contact Switching Action:

Breaks before makes each section in-line

Contact Load Current Rating:

100.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

NSN 5930-01-223-6415

Code Indicating Wheel Switch - Page 2 of 2



Contact	Arrangement	Truth	Table:

Bcd, 1 pole - 10 positions each section

Color:

Natural single body

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0