NSN 5930-01-223-7434

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-223-7434 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Corrosion resistant **Overall Length:** 3.570 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Body Diameter:** 1.000 inches **Bushing Length:** 0.540 inches **Case Material:** Metal **Actuator Style:** Round **Actuator Diameter:** 0.388 inches **Actuator Height:** Between 1.510 inches and 1.610 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained **Actuator Position-locking Relationship:** Up position locked in and down position no locking action **Maximum Voltage Rating In Volts:** 28.0 dc **Mounting Surface To Terminal End Distance:** 1.870 inches **Inclosure Type:** Fully enclosed

Mounting Method: Threaded bushing **Features Provided:** Holding solenoid Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches

NSN 5930-01-223-7434

Toggle Switch - Page 2 of 2



Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0