

View Online at <https://aerobasegroup.com/nsn/5930-01-223-7744>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.437 inches single mounting facility

**Overall Length:**

3.037 inches

**Overall Diameter:**

1.170 inches

**Individual Section Quantity:**

4

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

12 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 each section

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Contact Load Current Rating:**

75.0 milliamperes resistive load ac at sea level

**Special Features:**

Switch base, end plate and deck separator dap per mil-m-14; thermoplastic rotor mtg plate; terminals, base contacts and common plate brass, gold plate 0.00001 in min over silver plate 0.00003 in min; rotor contact silver alloy, gold plated 0.00001 in min; mtg hardware suppl1ed 2 mtg nuts 0.062 x 0.312 in and 1 internal tooth lockwasher

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0