

View Online at <https://aerobasegroup.com/nsn/5930-01-223-7744>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Overall Length:

3.037 inches

Overall Diameter:

1.170 inches

Individual Section Quantity:

4

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 each section front

Throw Quantity:

12 each section rear

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load ac at sea level

Special Features:

Switch base, end plate and deck separator dap per mil-m-14; thermoplastic rotor mtg plate; terminals, base contacts and common plate brass, gold plate 0.00001 in min over silver plate 0.00003 in min; rotor contact silver alloy, gold plated 0.00001 in min; mtg hardware suppl1ed 2 mtg nuts 0.062 x 0.312 in and 1 internal tooth lockwasher

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0