

View Online at <https://aerobasegroup.com/nsn/5930-01-223-9299>

**Hazardous Locations/environmental Protection:**

Moisture resistant and dust resistant and salt spray resistant

**Overall Length:**

2.760 inches

**Overall Height:**

1.770 inches

**Overall Width:**

1.150 inches

**Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

**Individual Section Quantity:**

4

**Longest Horizontal Distance Between Mounting Centers:**

2.590 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.900 inches single mounting facility

**Operating Temperature Range:**

-25.0 to 150.0 degrees fahrenheit

**End Application:**

5895-01-108-5631 satellite comm term

**Pole Quantity:**

1 each section in-line

**Throw Quantity:**

10 each section in-line

**Mounting Method:**

Bracket and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel all actuators

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

10 all actuators

**Terminal Type:**

Printed circuit

**Contact Switching Action:**

Breaks before makes each section in-line

**Contact Load Current Rating:**

100.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 each section

**Contact Arrangement Truth Table:**

Bcd, 1 pole - 10 positions each section

**Color:**

Natural single body

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0