

View Online at <https://aerobasegroup.com/nsn/5930-01-223-9808>

Body Style:

Panel mount

Body Length:

0.750 inches

Body Width:

0.750 inches

Body Height:

2.330 inches

Actuator Length:

0.658 inches

Actuator Style:

Rectangular

Actuator Height:

0.180 inches

Actuator Width:

0.658 inches

Actuator Color:

Green single actuator

Illuminated Actuator Color:

Green single actuator

Actuator Inscription:

Power, on single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

81349-mil-prf-22885/83 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-prf-22885 spec.