NSN 5930-01-223-9808



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-223-9808 **Body Style:** Panel mount **Body Length:** 0.750 inches **Body Width:** 0.750 inches **Body Height:** 2.330 inches **Actuator Length:** 0.658 inches **Actuator Style:** Rectangular **Actuator Height:** 0.180 inches **Actuator Width:** 0.658 inches **Actuator Color:** Green single actuator **Illuminated Actuator Color:** Green single actuator **Actuator Inscription:** Power, on single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 2 pole, double throw, both positions maintained single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac **Test Data Document:** 81349-mil-prf-22885/83 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 5 tab, solder lug and 6 turret Shelf Life: N/a **Unit Of Measure:**

Fiig:

No

Demilitarization:

NSN 5930-01-223-9808

Push Switch - Page 2 of 2



Mil-std (military Standard):

Mil-prf-22885 spec.