

View Online at <https://aerobasegroup.com/nsn/5930-01-224-1794>

Overall Length:

70.0 millimeters

Outside Diameter:

0.4375 inches single connection

Overall Height:

180.0 millimeters

Overall Width:

53.0 millimeters

Body Height:

80.0 millimeters

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -50.0 degrees celsius and 70.0 degrees celsius

Mounting Method:

Bracket

Contact Action Stimulus:

Decrease

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

16.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+0.00 to 0.50 actuation point inches of mercury and +2.00 to 10.00 deactuation point inches of mercury

Contact Adjustment Type:

Internal actuation point screw and internal actuation point screw with scale

Contact Stimulus Rating:

0.50 actuation point inches of mercury and 7.00 deactuation point inches of mercury and 0.50 differential point inches of mercury and 3.00 differential point inches of mercury

Contact Voltage Rating In Volts:

380.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded external single connection

Special Features:

Bracketed not supplied with item; lock plate available

Frequency In Hertz:

50.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0