

View Online at <https://aerobasegroup.com/nsn/5930-01-224-2445>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Overall Length:

2.625 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.188 inches single actuator

Shaft Diameter:

0.219 inches single actuator

Shaft Length:

0.406 inches single actuator

Overall Diameter:

1.188 inches

Nonturn Device Radius:

0.375 inches at 3:00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Slotted bushing at 3:00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

6 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level and 100.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0