NSN 5930-01-224-3647

Thermostatic Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-224-3647 |
|---|
| Thread Class: |
| 3a single threaded stud |
| Thread Direction: |
| Right-hand single threaded hole |
| Thread Length: |
| 0.430 inches single threaded stud |
| Overall Length: |
| 5.000 inches |
| Body Diameter: |
| 0.320 inches |
| Body Length: |
| 4.030 inches |
| End Application: |
| 4520-01-071-1773 humidifier, operating room (must) |
| Tempurature Sensing Element Type: |
| Internal sensor |
| Width Across Flats: |
| 0.750 inches |
| Mounting Method: |
| Threaded hole |
| Features Provided: |
| Tamper proof cap |
| Cubic Measure: |
| 1.400 cubic inches |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.438 inches single threaded stud |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Connector, receptacle |
| Contact Load Current Rating: |
| 1.0 amperes resistive load single voltage |
| Contact Adjustability: |
| Deactuation point not adjustable |
| Contact Stimulus Rating: |
| 250.00 actuation point degrees fahrenheit and 220.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit |
| Contact Voltage Rating In Volts: |
| 115.0 ac at sea level single voltage |
| |

Frequency In Hertz: 60.0 single voltage

NSN 5930-01-224-3647

Thermostatic Switch - Page 2 of 2



| Media For Which Designed: |
|--------------------------------------|
| Liquid |
| Style Designator: |
| Cylindrical w/flange |
| Thread Series Designator: |
| Unf single threaded stud |
| Purchase Description Identification: |
| 8264-72-156-2842 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A048b0