## NSN 5930-01-224-3649

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-224-3649

## **Hazardous Locations/environmental Protection:**

Humidity resistant and salt spray resistant and vibration resistant

**Overall Length:** 

1.180 inches

**Overall Height:** 

0.609 inches

**Body Diameter:** 

0.640 inches

**Body Height:** 

0.315 inches

**Unthreaded Mounting Hole Diameter:** 

0.109 inches

**Distance Between Mounting Facility Centers:** 

0.937 inches

**Tempurature Sensing Element Type:** 

Internal sensor

**Operating Tempurature Rating:** 

Between -20.0 degrees fahrenheit and 500.0 degrees fahrenheit

**Mounting Method:** 

Bracket and unthreaded hole

**Features Provided:** 

Hermetically sealed case

**Contact Action Stimulus:** 

Decrease

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally open, momentary action

**Terminal Type:** 

Tab, solder lug

**Contact Load Current Rating:** 

7.0 amperes resistive load third voltage

**Contact Adjustability:** 

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:** 

23.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:** 

30.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

**Precious Material And Location:** 

Contact surfaces silver

## NSN 5930-01-224-3649

Thermostatic Switch - Page 2 of 2



Precious Material:
Silver
Style Designator:
Disc w/flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0