

View Online at <https://aerobasegroup.com/nsn/5930-01-224-3649>

Hazardous Locations/environmental Protection:

Humidity resistant and salt spray resistant and vibration resistant

Overall Length:

1.180 inches

Overall Height:

0.609 inches

Body Diameter:

0.640 inches

Body Height:

0.315 inches

Unthreaded Mounting Hole Diameter:

0.109 inches

Distance Between Mounting Facility Centers:

0.937 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -20.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

7.0 amperes resistive load third voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

23.00 actuation point degrees fahrenheit and 50.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0