

View Online at <https://aerobasegroup.com/nsn/5930-01-224-3654>

Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

2.770 inches

Overall Height:

0.750 inches

Overall Width:

Between 0.750 inches and 0.760 inches

Body Width:

Between 0.750 inches and 0.760 inches

Body Height:

0.750 inches

Case Material:

Metal

Actuator Length:

Between 0.590 inches and 0.650 inches

Actuator Style:

Rectangular

Actuator Height:

0.104 inches

Actuator Width:

Between 0.590 inches and 0.650 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Actuator Inscription:

Lamp test single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

2.620 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0