

View Online at <https://aerobasegroup.com/nsn/5930-01-224-3655>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

Between 0.750 inches and 0.760 inches

Overall Height:

2.770 inches

Overall Width:

Between 0.750 inches and 0.760 inches

Body Length:

0.688 inches

Body Width:

Between 0.750 inches and 0.760 inches

Body Height:

2.546 inches

Case Material:

Metal

Actuator Length:

Between 0.590 inches and 0.650 inches

Actuator Style:

Rectangular

Actuator Height:

0.104 inches

Actuator Width:

Between 0.590 inches and 0.650 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

Green single actuator and green single actuator

Actuator Inscription:

Deep scuttle single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Horizontal split lens

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0