## NSN 5930-01-224-5362

Push Switch - Page 1 of 1

A053a0



View Online at https://aerobasegroup.com/nsn/5930-01-224-5362 **Body Style:** Panel mount **Body Diameter:** 0.688 inches **Body Height:** 2.620 inches **Actuator Length:** 0.750 inches **Actuator Style:** Rectangular **Actuator Width:** 0.750 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac **Test Data Document:** 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 6 turret and 5 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: