

View Online at <https://aerobasegroup.com/nsn/5930-01-224-6486>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Humidity resistant and explosion proof and shock proof and vibration resistant

Overall Length:

0.750 inches

Overall Height:

2.035 inches

Overall Width:

0.750 inches

Body Length:

0.688 inches

Body Width:

0.688 inches

Body Height:

1.935 inches

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.095 inches and 0.100 inches

Actuator Width:

0.620 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Amber single actuator and green single actuator and red single actuator

Actuator Inscription:

Sel single actuator

Illuminated Actuator Color Sequence:

Upper half of actuator red lower half of actuator amber and green

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

Special Features:

Horizontally split screen, legend also contains symbol for greek letter omega

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

6 printed circuit and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0