

View Online at <https://aerobasegroup.com/nsn/5930-01-224-6486>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Humidity resistant and explosion proof and shock proof and vibration resistant

**Overall Length:**

0.750 inches

**Overall Height:**

2.035 inches

**Overall Width:**

0.750 inches

**Body Length:**

0.688 inches

**Body Width:**

0.688 inches

**Body Height:**

1.935 inches

**Actuator Length:**

0.620 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.095 inches and 0.100 inches

**Actuator Width:**

0.620 inches

**Actuator Color:**

Black single actuator

**Illuminated Actuator Color:**

Amber single actuator and green single actuator and red single actuator

**Actuator Inscription:**

Sel single actuator

**Illuminated Actuator Color Sequence:**

Upper half of actuator red lower half of actuator amber and green

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Special Features:**

Horizontally split screen, legend also contains symbol for greek letter omega

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

6 printed circuit and 6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0