## NSN 5930-01-224-6561

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-224-6561

| Body Style:  |
|--|
| Panel mount  |
| Overall Length:  |
| Between 0.750 inches and 0.760 inches  |
| Overall Height:  |
| 2.944 inches   |
| Overall Width:   |
| Between 0.750 inches and 0.760 inches  |
| Body Length:   |
| 0.688 inches   |
| Body Width:  |
| 0.688 inches   |
| Body Height:   |
| 2.620 inches   |
| Actuator Length:   |
| Between 0.590 inches and 0.650 inches  |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 0.150 inches   |
| Actuator Width:  |
| Between 0.590 inches and 0.650 inches  |
| Actuator Color:  |
| White single actuator  |
| Illuminated Actuator Color:  |
| White single actuator and white single actuator  |
| Actuator Inscription:  |
| Test, off single actuator  |
| Maximum Voltage Rating In Volts:   |
| 115.0 ac and 28.0 dc   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Nonpile-up Contact Arrangement:  |
| 4 pole, double throw, both positions maintained single switch unit   |
| Contact Load Current Rating At Maximum Rated Voltage:  |
| 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes |
| inductive ac and 2.000 amperes lamp ac   |
| Special Features:  |
| Split lens   |

**Terminal Type And Quantity:** 12 turret and 5 tab, solder lug

## NSN 5930-01-224-6561

Push Switch - Page 2 of 2



| C | ha  | Ιf | 1 | ife   |  |
|---|-----|----|---|-------|--|
| • | ııe |    | _ | .II C |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0