NSN 5930-01-224-6561

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-224-6561

| Body Style: |
|--|
| Panel mount |
| Overall Length: |
| Between 0.750 inches and 0.760 inches |
| Overall Height: |
| 2.944 inches |
| Overall Width: |
| Between 0.750 inches and 0.760 inches |
| Body Length: |
| 0.688 inches |
| Body Width: |
| 0.688 inches |
| Body Height: |
| 2.620 inches |
| Actuator Length: |
| Between 0.590 inches and 0.650 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.150 inches |
| Actuator Width: |
| Between 0.590 inches and 0.650 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| White single actuator and white single actuator |
| Actuator Inscription: |
| Test, off single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes |
| inductive ac and 2.000 amperes lamp ac |
| Special Features: |
| Split lens |

Terminal Type And Quantity: 12 turret and 5 tab, solder lug

NSN 5930-01-224-6561

Push Switch - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0