

View Online at <https://aerobasegroup.com/nsn/5930-01-224-7047>

**Overall Length:**

Between 0.894 inches and 0.962 inches

**First Flat Length:**

0.230 inches single actuator and 0.270 inches single actuator

**Mounting Slot Width:**

0.064 inches single mounting facility and 0.068 inches single mounting facility

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.896 inches single actuator and 0.936 inches single actuator

**Overall Diameter:**

Between 1.115 inches and 1.135 inches

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Slotted bushing at 4: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

16 single section front

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 highest dc voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

22.5 degrees single actuator

**Contact Load Current Rating:**

75.0 milliamperes resistive load highest dc voltage rating at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0