

View Online at <https://aerobasegroup.com/nsn/5930-01-224-7047>

Overall Length:

Between 0.894 inches and 0.962 inches

First Flat Length:

0.230 inches single actuator and 0.270 inches single actuator

Mounting Slot Width:

0.064 inches single mounting facility and 0.068 inches single mounting facility

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.896 inches single actuator and 0.936 inches single actuator

Overall Diameter:

Between 1.115 inches and 1.135 inches

Individual Section Quantity:

1

Nonturn Device Type:

Slotted bushing at 4: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

16 single section front

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 highest dc voltage rating at sea level

Switch Actuator Indexing Position Quantity:

16 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

22.5 degrees single actuator

Contact Load Current Rating:

75.0 milliamperes resistive load highest dc voltage rating at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0