NSN 5930-01-225-1177



Thermostatic Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-01-225-1177 **Overall Length:** 1.200 inches **Overall Height:** 0.375 inches **Body Diameter:** 0.630 inches **Body Height:** 0.355 inches **Unthreaded Mounting Hole Diameter:** 0.141 inches **Distance Between Mounting Facility Centers:** 0.937 inches **Tempurature Sensing Element Type:** Internal sensor **Mounting Method:** Bracket and unthreaded hole **Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally open, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 0.5 amperes resistive load second voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 165.00 actuation point degrees fahrenheit and 135.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage Frequency In Hertz: 400.0 first voltage Media For Which Designed: Gas or liquid **Style Designator:** Disc w/flange Shelf Life:

N/a

Unit Of Measure:

NSN 5930-01-225-1177

Thermostatic Switch - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A048b0