## NSN 5930-01-225-7491

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-225-7491

Center To Center Distance Between Mounting Facilities Parallel To Length:
22.2 millimeters
Body Length:
31.7 millimeters
Body Width:
10.5 millimeters
Body Height:
19.9 millimeters
Unthreaded Mounting Hole Diameter:
0.3 millimeters
Center To Center Distance Between Mounting Facilities Parallel To Height:
10.2 millimeters
Actuator Length:
2.4 millimeters
Actuator Style:
Rectangular
Actuator Height:
2.8 millimeters
Actuator Width:
2.4 millimeters
Maximum Voltage Rating In Volts:
250.0 ac
End Application:
2910-01-215-0459 governor, diesel engine onboard 110 ft wpb coast guard vessels
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Switch Release Force:
4.0 ounces
Switch Actuating Force:
14.0 ounces
Actuator Movement:
1.4 pretravel millimeters and 1.4 overtravel millimeters and 0.4 differential millimeters
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Terminal Type And Quantity:
3 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-01-225-7491

Sensitive Switch - Page 2 of 2



em			

No

Fiig:

A053a0