NSN 5930-01-225-8936

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-225-8936 **Overall Length:**

Overall Height:

1.650 inches

5.545 inches

Overall Width:

1.650 inches

Unthreaded Mounting Hole Diameter:

0.188 inches single mounting facility

Distance Between Mounting Facility Centers:

1.188 inches single mounting facility

Individual Section Quantity:

7

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Unthreaded hole single mounting facility

Features Provided:

Actuator knob and cam actuated

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Three position in-line single mounting facility

Cam Actuated Switch Contact Arrangement:

1 pole, single throw, double make, both positions maintained each switch each section periphery

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load lowest dc voltage rating at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

In-line, cam actuated

Shelf Life:

N/a

Unit Of Measure:

NSN 5930-01-225-8936

Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0