

View Online at <https://aerobasegroup.com/nsn/5930-01-225-8940>

**Body Style:**

Panel mount

**Overall Length:**

0.800 inches

**Overall Height:**

1.890 inches

**Overall Width:**

0.800 inches

**Body Length:**

0.745 inches

**Body Width:**

0.745 inches

**Body Height:**

1.700 inches

**Actuator Length:**

0.600 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.130 inches

**Actuator Width:**

0.600 inches

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

120.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 3.000 amperes inductive ac

**Test Data Document:**

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 quick disconnect, male

**Specification Data:**

81349-mil-s-22885/93 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0