

View Online at <https://aerobasegroup.com/nsn/5930-01-225-8941>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

1.888 inches

**Overall Height:**

0.620 inches

**Overall Width:**

0.620 inches

**Body Diameter:**

0.620 inches

**Bushing Length:**

0.440 inches

**Body Length:**

1.000 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.380 inches

**Actuator Height:**

0.280 inches

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.500 amperes inductive dc and 0.500 amperes lamp dc and 2.000 amperes resistive ac and 1.500 amperes inductive ac and 0.500 amperes lamp ac

**Precious Material And Location:**

Contact and terminal surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0