NSN 5930-01-225-9353

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-225-9353

Thread Class:

2a single mounting facility

Individual Section Quantity:

14

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.180 inches single mounting facility

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

500.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

5 single actuator

Terminal Type:

Screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Special Features:

Escutcheon engraved with shore, gen, off, bt3-2, bt3-1

Precious Material And Location:

Rotor and stator surfaces silver

Precious Material:

Silver

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5930-01-225-9353 Rotary Switch - Page 2 of 2

Fiig: A052b0

