

View Online at <https://aerobasegroup.com/nsn/5930-01-225-9353>

**Thread Class:**

2a single mounting facility

**Individual Section Quantity:**

14

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.180 inches single mounting facility

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Terminal Type:**

Screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:**

Escutcheon engraved with shore, gen, off, bt3-2, bt3-1

**Precious Material And Location:**

Rotor and stator surfaces silver

**Precious Material:**

Silver

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0