## NSN 5930-01-225-9353

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-225-9353

**Thread Class:** 

2a single mounting facility

**Individual Section Quantity:** 

14

**Longest Horizontal Distance Between Mounting Centers:** 

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:** 

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

2.180 inches single mounting facility

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:** 

Actuator knob and legend plate

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:** 

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

Terminal Type:

Screw

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:** 

Escutcheon engraved with shore, gen, off, bt3-2, bt3-1

**Precious Material And Location:** 

Rotor and stator surfaces silver

**Precious Material:** 

Silver

**Thread Series Designator:** 

Unf single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

## **NSN 5930-01-225-9353**Rotary Switch - Page 2 of 2



Fiig:

A052b0