

View Online at <https://aerobasegroup.com/nsn/5930-01-226-0459>

Thread Class:

2b

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.575 inches

Overall Height:

1.310 inches

Overall Width:

0.345 inches

Bushing Length:

0.250 inches

Body Length:

0.575 inches

Body Width:

0.345 inches

Body Height:

0.540 inches

Actuator Style:

Round

Actuator Diameter:

0.110 inches

Actuator Height:

0.420 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 2.000 amperes inductive ac and 1.000 amperes lamp ac

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 turret

Specification Data:

96906-ms27716 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0